


▶ PRODUCT ADVANTAGES



▶ TECHNICAL DETAILS



▶ INFORMATION ON THE PRODUCTS

APPLICATION SCENARIOS

- ▶ Torque take-up of shafts
- ▶ Safety clamping of the torque motor
- ▶ Clamping of C-axis
- ▶ Fixing and safeguarding of swivel bridge
- ▶ Clamping of spindle tilting axis
- ▶ Clamping of the swiveling axis for portals


▶ RECOMMENDED ACCESSORIES



ZDKPS1000-SH
Sensor mounting kit

► TECHNICAL DRAWINGS

Ⓐ Connection opening



► TECHNICAL DATA

Order no.	DKPS1140-00-A
Operation	pneumatic
Holding torque [Nm]	770
Theoretical holding torque ($\mu=0,1$) [N]	963
Operating pressure [bar]	5.5 ... 6.5
B10d value	3,000,000
Opening time [s]	0.1
Closing time [s]	0.1
Operating temperature [°C]	5 ... +80
Weight [kg]	5.2
Shaft Ø [mm]	140
Function	Clamping
Condition	NC (Normally Closed) closed without pressure
Installation direction	from the front
Air volume per cycle [cm ³]	60
Sensor linkage	Optional
Certifications	CE / UKCA / LABS / REACH / RoHS

Schematic drawing. General tolerances according to DIN ISO 2768 T1-/T2-H. Edges according to ISO 13715. The holding torque is the maximum torque that can be applied rotationally. Each rotary clamping element is tested for the specified holding torque with a lightly oiled lubricating layer (ISO-VG 68) in a 100% inspection before delivery. The use of other lubricants can influence the coefficient of friction. The operating instructions must be observed before commissioning. We reserve the right to make technical changes in the course of further development. The latest and further data can be found online and in the operating instructions at www.zimmer-group.com.